



# LIVAL

## BING PRO DL

- Rotating
- Tilting
- Light Channel
- Thermally Strong
- Reflectors: 15D, 21D, 32D
- Available Drivers: ON / OFF, Dali, Casambi

### Technical data

| Input Power | LED-Module                      | Color Consistency | Installation Type | Material                             | Lumen Maintenance  | Luminaire Color  |
|-------------|---------------------------------|-------------------|-------------------|--------------------------------------|--------------------|--|
| 220-240V    | PHILIPS-<br>SAMSUNG-<br>CITIZEN | 2-Step<br>MacAdam | Downlight         | Powder Painted Die-<br>Cast Aluminum | 50 000h L80<br>B10 | White (RAL 9016) Silver (Ca.<br>RAL 9006) Black (RAL 9005) |

| COB Type     | Forward current | System Luminous Flux | System Power | Lm/W  |
|--------------|-----------------|----------------------|--------------|-------|
| CRI 90 3000K | 250mA           | 1 240 lm             | 10,0 W       | 124.0 |
| CRI 90 3000K | 650mA           | 3 090 lm             | 25,4 W       | 121.6 |
| CRI 90 3000K | 750mA           | 3 519 lm             | 29,4 W       | 119.7 |
| CRI 90 4000K | 250mA           | 1 300 lm             | 10,0 W       | 130.0 |
| CRI 90 4000K | 650mA           | 3 265 lm             | 25,4 W       | 128.5 |
| CRI 90 4000K | 750mA           | 3 725 lm             | 29,4 W       | 126.7 |

