



**LIVAL**  
**DINGO PRO DL**

- Rotating
- Tilting
- Light Channel
- Thermally Strong
- Reflectors: 15D, 28D, 50D
- Available Drivers: ON / OFF, Dali, Casambi

**Technical data**

Input Power	LED-Module	Color Consistency	Installation Type	Material	Lumen Maintenance	Luminaire Color
-------------	------------	-------------------	-------------------	----------	-------------------	-----------------

220-240V	PHILIPS- SAMSUNG- CITIZEN	2-Step MacAdam	Downlight	Powder Painted Die- Cast Aluminum	50 000h L80 B10	White (RAL 9016) Silver (Ca. RAL 9006) Black (RAL 9005)
----------	---------------------------------	-------------------	-----------	--------------------------------------	--------------------	--

COB Type 1208	Forward current	System Luminous Flux	System Power	Lm/W
CRI 90 3000K	250mA	1 240 lm	10,0 W	124.0
CRI 90 3000K	650mA	3 090 lm	25,4 W	121.6
CRI 90 3000K	1 050mA	4 736 lm	41,8 W	113.3
CRI 90 4000K	250mA	1 300 lm	10,0 W	130.0
CRI 90 4000K	650ma	3 265 lm	25,4 W	128.5
CRI 90 4000K	1 050mA	5 030lm	41,8 W	120.4

